



SELF-SERVICE WASHING SYSTEMS FOR 1-3 WASHING BAYS, CABINET VERSION,
OUTDOOR, OIL-, GAS-, WITH DISTRICT OR ELECTRICALLY HEATING

JetWash/JetWash PLUS



Standard equipment JetWash/JetWash PLUS

The JetWash systems are equipped with four standard cleaning and care programmes. There is the option of combining the self-service system with additional programmes. The JetWash appliance series are available up to system variant 3SE and the JetWash PLUS appliance series up to system variant 10. The JetWash/JetWash PLUS appliances can be combined with all EHRLE payment systems; CentralPay technology is also available as an option. The entire washing technology is housed in a stainless steel frame with powder-coated appliance panelling. JetWash and JetWash PLUS units can be heated either with oil, gas, district heating or electricity.

Further equipment

Like every self-service car wash system from EHRLE, the JetWash systems are equipped with a water softener (ion exchanger). In addition, the JetWash PLUS version has a reverse osmosis system with an 800 litre osmosis water tank. The reverse osmosis prevents water stains after washing and drying. The washing system is controlled by a modern SIEMENS computer. The 7-inch TFT touchscreen monitor installed in the control system gives the investor access to all information about the important parameters of the self-service car wash system and provides detailed financial information about revenue and turnover.

JW

JetWash



JW+

JetWash PLUS





SELF-SERVICE WASHING SYSTEMS FOR 1-3 WASHING BAYS, CABINET
VERSION, OUTDOOR, OIL-, GAS-, WITH DISTRICT OR ELECTRICALLY HEATING

JetWash/JetWash PLUS



Type	1-3 wash bays oil			1-3 wash bays gas			1-3 wash bays district heating			1-3 wash bays electrical		
Wash bays	1 WP	2 WP	3 WP	1 WP	2 WP	3 WP	1 WP	2 WP	3 WP	1 WP	2 WP	3 WP
Voltage	3/PE/AC/50Hz/400V			3/PE/AC/50Hz/400V			3/PE/AC/50Hz/400V			3/PE/AC/50Hz/400V		
Operating pressure per wash bay	120bar/12Mpa			120bar/12Mpa			120bar/12Mpa			120bar/12Mpa		
Max. pressure per wash bay	140bar/14Mpa			140bar/14Mpa			140bar/14Mpa			140bar/14Mpa		
Discharge capacity per wash bay	660l/h			660l/h			660l/h			660l/h		
Nozzle size	60056			60056			60056			60056		
Hot water capacity	60°C			60°C			60°C			60°C		
Heat output	50kW	50kW	55kW	55kW	55kW	74kW	50kW	55kW	74kW	18kW	24kW	36kW
Pump speed	900U/min			900U/min			900U/min			900U/min		
Water softening capacity	120m ³			120m ³			120m ³			120m ³		
Permeate output reverse osmosis	-			-			-			-		
Contents of osmosis tank	-			-			-			-		
Contents MicroPowder dispenser tank	35l			35l			35l			35l		
Contents UltraProtection tank	10l			10l			10l			10l		
Contents SuperFinish tank	10l			10l			10l			10l		
Connected load	5kW	8kW	11kW	5kW	8kW	11kW	5kW	8kW	11kW	23kW	32kW	41kW
Electrical protection	3x10A	3x16A	3x25A	3x10A	3x16A	3x25A	3x10A	3x16A	3x25A	3x50A	3x63A	3x63A
Weight net	910kg	950kg	990kg	910kg	950kg	990kg	910kg	950kg	990kg	910kg	950kg	990kg
Dimensions device (LxWxH)	1WP: 2245x970x2100mm 2+3WP: 2270x970x2100mm			1WP: 2245x970x2100mm 2+3WP: 2270x970x2100mm			1WP: 2245x970x2100mm 2+3WP: 2270x970x2100mm			1WP: 2245x970x2100mm 2+3WP: 2270x970x2100mm		



SELF-SERVICE WASHING SYSTEMS FOR 1-3 WASHING BAYS, CABINET
VERSION, OUTDOOR, OIL-, GAS-, WITH DISTRICT OR ELECTRICALLY HEATING

JetWash/JetWash PLUS



Type	1-3 wash bays oil			1-3 wash bays gas			1-3 wash bays district heating			1-3 wash bays electrical		
Wash bays	1 WP	2 WP	3 WP	1 WP	2 WP	3 WP	1 WP	2 WP	3 WP	1 WP	2 WP	3 WP
Voltage	3/PE/AC/50Hz/400V			3/PE/AC/50Hz/400V			3/PE/AC/50Hz/400V			3/PE/AC/50Hz/400V		
Operating pressure per wash bay	120bar/12Mpa			120bar/12Mpa			120bar/12Mpa			120bar/12Mpa		
Max. pressure per wash bay	140bar/14Mpa			140bar/14Mpa			140bar/14Mpa			140bar/14Mpa		
Discharge capacity per wash bay	660l/h			660l/h			660l/h			660l/h		
Nozzle size	60056			60056			60056			60056		
Hot water capacity	60°C			60°C			60°C			60°C		
Heat output	50kW	50kW	55kW	55kW	55kW	74kW	50kW	55kW	74kW	18kW	24kW	36kW
Pump speed	900U/min			900U/min			900U/min			900U/min		
Water softening capacity	120m³			120m³			120m³			120m³		
Permeate output reverse osmosis	7.200l/da at 12°C water temp.			7.200l/da at 12°C water temp.			7.200l/da at 12°C water temp.			7.200l/da at 12°C water temp.		
Contents of osmosis tank	800l			800l			800l			800l		
Contents MicroPowder dispenser tank	35l			35l			35l			35l		
Contents UltraProtection tank	10l			10l			10l			10l		
Contents SuperFinish tank	10l			10l			10l			10l		
Connected load	6kW	9kW	12kW	6kW	9kW	12kW	6kW	9kW	12kW	24kW	33kW	42kW
Electrical protection	3x16A	3x20A	3x25A	3x16A	3x20A	3x25A	3x16A	3x20A	3x25A	3x50A	3x63A	3x63A
Weight net	1200kg	1300kg	1360kg	1200kg	1300kg	1360kg	1200kg	1300kg	1360kg	1200kg	1300kg	1360kg
Dimensions device (LxWxH)	1WP: 3250x970x2100mm 2+3WP: 3275x970x2100mm			1WP: 3250x970x2100mm 2+3WP: 3275x970x2100mm			1WP: 3250x970x2100mm 2+3WP: 3275x970x2100mm			1WP: 3250x970x2100mm 2+3WP: 3275x970x2100mm		